

Settings Yaesu FT-991A

Red marking is menus that has been changed from default

1	300msec	31	38400bps	61	15msec	91	on	121	7	151
2	700msec	32	100msec	62	others	92	300Hz	122	1000	152
3	3000msec	33	disable	63	1000Hz	93	18db/oct	123	7	153
4	Funktion	34	disable	64	1500Hz	94	3000Hz	124	8	
5	3sec	35	5kHz	65	1500Hz	95	18db/oct	125	2000	
6	green	36	10min	66	off	96	Shift	126	5	
7		2	enable	67	18db/oct	97	nor	127	5	
8		15	time	68	off	98	nor	128	100	
9	2.0sec	39		0	69	18db/oct	99	50	129	6
10		50	rx	70	rear	100	170Hz	130	1	
11		50	off	71	RTS	101	2125Hz	131	700	
12	off	42	6db/oct	72	USB	102	100Hz	132	-3	
13	nor	43	off	73		50	103	6db/oct	133	1
14	3.0	44	6db/oct	74	mic	104	3400Hz	134	2700	
15	off	45	mic	75		50	105	6db/oct	135	10
16		1290		50	76	daky	106	Rear	136	1
17		0	daky	47	77	data	107	80	137	100
18	text	48	data	78		50	108	RTS	138	100
19	text	49		50	79	1200	109	USB	139	21
20	text	50	250Hz	80	100kHz	110	100-3000	140	50	
21	text	51	18db/oct	81	500kHz	111	narrow	141	internal	
22	text	52	1200Hz	82	600kHz	112	-15	142	mic	
23	3msec	53	18db/oct	83	7600kHz	113	10	143	57	
24	30db	54		50	84	on	114	wide	144	300msec
25		5	on	55	85	on	115	water fall	145	50
26		0	semi	56	86	TN-Rn	116	1000kHz	146	50
27	+1:00	57	200msec	87	Gobal	117	green	147	100msec	
28	RS232C	58	4msec	88	distance	118	Multi	148	0	
29	38400bps	59	Direct freq	89	km	119	500	149	disable	
30	10msec	60	RTS	90	manual	120	8	150	manual	

Settings with : MD-100
JTDX
N1MM logger+

If working with FH-2 106 has to be set to MIC when recording

